


Discharge Data


Constant Current Discharge Data (25°C, A)												
End Voltage (V/cell)	min					h						
	10	15	20	30	45	1	1.5	2	3	5	10	20
1.60	115.0	92.50	75.00	56.00	41.12	29.78	23.67	18.99	13.50	8.927	5.325	2.715
1.65	111.0	88.91	73.13	54.56	40.00	29.09	22.88	18.56	13.25	8.792	5.250	2.675
1.67	108.7	87.86	72.14	54.02	39.58	28.75	22.61	18.38	13.17	8.729	5.210	2.657
1.70	106.0	86.45	70.87	53.27	39.01	28.42	22.24	18.13	13.03	8.632	5.170	2.640
1.75	101.3	83.45	68.31	51.74	37.82	27.50	21.57	17.67	12.80	8.500	5.100	2.600
1.80	96.00	79.93	66.24	50.00	36.50	26.38	20.94	17.21	12.50	8.294	5.000	2.520

Constant Power Discharge Data (25°C, W/cell)												
End Voltage (V/cell)	min					h						
	10	15	20	30	45	1	1.5	2	3	5	10	20
1.60	206.8	159.5	139.0	111.9	81.50	61.74	48.72	37.75	26.52	18.50	10.92	5.655
1.65	198.9	156.3	135.9	109.2	78.95	59.70	47.63	36.96	25.90	18.20	10.69	5.540
1.67	196.1	155.2	134.4	107.8	78.17	59.02	47.13	36.54	25.63	17.93	10.59	5.491
1.70	192.5	153.4	132.3	105.9	77.08	58.03	46.44	35.97	25.31	17.59	10.42	5.435
1.75	186.1	149.6	129.2	102.8	74.60	56.27	45.00	34.58	24.45	16.90	10.25	5.280
1.80	177.4	145.7	125.5	97.83	71.94	54.17	43.50	33.40	23.56	16.50	9.890	5.100


Performance Curve




Discharge voltage vs. discharge time



Charge capacity vs. charge time



Discharge capacity vs. temperature



Design life vs. temperature



Disclaimer: The manufacturer reserves the right to amend and/or vary the specifications and parameters of the product and apply updates accordingly at any time. It is the sole responsibility of the buyer and user of the product to ensure all applicable product specifications referred to are valid and up to date. All product specifications are available upon request. Batteries must be installed in accordance with standard BS EN IEC 62485-2:2018, and in accordance with manufacturer's guidelines. (available upon request)